

## BULL'S EYE

FOOD GRADE SILICONE LUBRICANT  
*Lubricante de silicona de grado alimenticio*

SUNRISE' BULL'S EYE is a non-staining, stable blended formula that deeply penetrates, thus eliminating sticking problems and annoying squeaks. BULL'S EYE will repel water and ice and retard rust and corrosion. It will lubricate and free sticking windows, doors, drawers, zippers, cabinets, etc. Also, may be used on rubber, leather, metal, nylon, wood and painted surfaces. Do not apply directly to food. This can be used on food processing equipment  
Note: This product contains a solution of saturated aliphatic hydrocarbons. Addition to food not to exceed 1 part per million. The silicone ingredient is in the code of Federal Regulations of the FDA, in 21 CFR part 178.3570.

### DIRECTIONS

Shake well before use!

For additional information including SDS and Tech Data Sheet scan QR code here →



### FEATURES:

- NSF Rated : H1
- Non-Staining
- Repels water and ice
- Long lasting
- High quality silicone

### SUGGESTED USES:

- Ovens
- Chains
- Hinges
- Food processing machinery



# BULL'S EYE

## FOOD GRADE SILICONE LUBRICANT

PRODUCT #1109

NET WEIGHT: 13.25 OZ (386 g)

**CAUTION:** CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

**KEEP OUT OF REACH OF CHILDREN**

### CAUTIONS

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

### INGREDIENTS

Aliphatic Petroleum Distillate 64742-47-8, Hydrotreated Light Distillated 64742-47-8, Isoparaffinic Hydrocarbon 64742-47-8, Hydrocarbon Propellant 68-476-86-8, Silicone Emulsion 63148-62-9, p-Metha-1,8-diene 5989-27-5, Orange Oil 8008-57-9

### HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

### H.M.I.S.

Toxicity: 1 Fire: 1 Reactivity: 0 Special: N.A

### Hazard Symbol(s)



### TRANSPORT INFORMATION

U.N. Number: UN 1950

U.N. Proper Shipping Name: Aerosol, Flammable

Transport Hazard Class(es): 2.1

Description: UN 1950, Aerosols, Flammable, 2.1, Limited Quantity



Nonfood Compounds  
Program Listed H1  
(Registration #145312)

**SUNRISE ENVIRONMENTAL SCIENTIFIC**

800-648-1153 SUNRISENV.COM



PO BOX 10207  
RENO NV, 89510

*Since 1975*