

## SAFETY SECTION

### CAS#

108-88-3  
64742-96-7  
1330-20-7  
8002-74-2  
68-476-86-8  
67-64-1



### SCAN FOR INFORMATION



TECH + SAFETY DATA

### DANGER...

- FATAL OR TOXIC IF SWALLOWED
- RESPIRATORY TRACT IRRITANT
- MAY CAUSE SKIN IRRITATION OR BURN



### ~ FEATURES ~

- Rinses with water
- Attacks all greases and oils.
- Powerful solvent stream, quickly flushes away grease and grime.

### ~ USE ON ~

- Tools • Machinery
- Automobile • Trucks
- Tractors • Marine Engines • Painted surfaces

ORM-D CONSUMER COMMODITY CLASS 55



PO Box 10207 ~ Reno, Nevada ~ 89510

# NOT FOR RESALE

## SUNRISE

### ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

# FLUSH OFF

**SPRAY ON GREASE, OIL OR DIRT  
THEN HOSE OFF WITH WATER**

\* DESENGASANTE SOLUBLE EN AGUA \*

NET WEIGHT 14.5 OZ

SHAKE WELL BEFORE USING!

**CAUTION: FLAMMABLE**  
Contents under pressure. Vapor may be harmful.  
Read cautions on backpanel before using.  
**KEEP OUT OF REACH OF CHILDREN**

## FLUSH OFF #1040

**FLUSH OFF** is a mixture of emulsifiable solvents and fast action additives. This solution saves man hours by flushing sludge and greasy residue from metal and painted surfaces quickly and safely. It has proved especially valuable to machine repair depots, street and highway departments, industrial plants, factories and school bus garages. Saves maintenance and repair time.

**DIRECTIONS:** **FLUSH OFF** is a quick-acting cleaner which easily removes grease, dirt and oil deposits from painted surfaces, tools, machinery, automobiles, trucks, tractors and marine engines. Hold can upright, point spray opening at surface to be cleaned and press down on valve. For best results allow the **FLUSH OFF** to penetrate for 10 minutes and then flush thoroughly with water. If further cleaning is necessary, repeat application and rinse again with water. Where hard or thick deposits are encountered, remove excess grease, oil, tars or sludge with a putty knife or scraper prior to spraying. Before using on a painted surface make a test by spraying a small inconspicuous area to insure that the paint will not be affected.

**CAUTION:** The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. **FLAMMABLE.** Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Warning: Under Proposition 65, this product contains a chemical known to the State of California to cause birth defects or other reproductive harm. Consult Safety Data Sheet for additional information.



800-648-1153 WWW.SUNRISENV.COM

**SUNRISE ENVIRONMENTAL SCIENTIFIC**