

LUBRON

"Grease Gun in a Can"
LUBRICANTE, PENETRANTE, ANTICORROSIVO

This state-of-the-art product sprays on and into hard-to-reach places. Once fully cured LUBRON becomes a tough, protective grease. This cured film is impervious to moisture and is stable at temperatures above 400°F. It will lubricate and prevent rust on any metallic surface.

DIRECTIONS

Spray a thin film on the surface to be lubricated or protected. To treat hard-to-reach areas, insert extension tube in spray tip. LUBRON will start forming into a grease in seconds. Allow 15 to 20 minutes for product to fully cure.

For additional information including SDS and Tech Data Sheet scan QR code here →



USE ON:

- Tools, Slides
- Power Mowers
- Tracks
- Machinery
- Equipment

Features:

- Red Grease
- Lubricant, Penetrant & Rust Preventative
- Clings to Vertical Surfaces
- Non-Staining



"Grease Gun in a Can"
LUBRON
LUBRICANT

PRODUCT #1055

NET WEIGHT: 13.75 OZ (395 g)

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

CAUTIONS

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

INGREDIENTS

n-Hexane 110-54-3, Isoparaffinic Hydrocarbon 84742-47-8, Hydrocarbon Propellant 68-476-86-8, Polydimethyl Siloxane 63148-62-9

HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity: 1 Fire: 3 Reactivity: 0 Special: N.A

Hazard Symbol(s)



TRANSPORT INFORMATION

U.N. Number: UN1950

U.N. Proper Shipping Name: Aerosol, Flammable

Transport Hazard Class(es): 2.1

Description: UN1950, Aerosols, Flammable, 2.1, Limited Quantity

SUNRISE ENVIRONMENTAL SCIENTIFIC

800-648-1153 SUNRISENV.COM



PO BOX 10207
RENO NV, 89510

Since 1975