



# SAFETY DATA SHEET



## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Chemical Name: 911 PRUNING SEAL

Product Number: 1099

Manufacturer Information: Sunrise Environmental Scientific

Remit: PO Box 10207 Reno, NV 89510

Physical: 1175 Industrial Way Sparks, NV 89431

Phone Number: 775-359-8494 or 800-648-1153

Pages: 3

Web: SUNRISENV.COM

Application: PRUNING, GRAFTING AND TREE SEALANT

UN-Number: N/A

Emergency Phone No.

Chemtrec: 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Emergency Overview:

Signal Word: DANGER

Keep out of reach of children.

### Potential Health Effects:

Inhalation: Excessive inhalation of vapors may cause irritation of the respiratory tract, nausea, dizziness and/or headache.

Skin Contact: Prolonged contact may cause irritation and/or dryness of skin.

Ingestion: May cause serious health effects including vomiting, nausea and/or gastrointestinal irritation.



## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient:	CAS #	Component WT%	PEL	TLV	IDLH
Calcium Carbonate	1317-65-3	5%≤40%	N/A	N/A	N/A
Asphalt	8052-42-4	5%≤25%	N/A	0.5*mg/m3	N/A
*Toluene	108-88-3	6%≤22%	100 ppm	100 ppm	N/A
VM&P Naphta	64742-89-8	4%≤15%	ND	ND	ND
Talc	14807-96-6	4%≤13%	ND	ND	ND
Propane	74-98-6	4%≤15%	1000 ppm	Appendix F	N/A
n-butane	106-97-8	3%≤17%	ND	1000 ppm	ND

Comments: None

## 4. FIRST AID MEASURES

Inhalation: If affected by vapors, move to a well ventilated area immediately. If breathing is difficult seek physician help.

Skin Contact: Flush with water, immediately remove all contaminated clothing.

Ingestion: Do not induce vomiting and seek physician care.

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue for at least 15 minutes and seek physician help.

Additional Information: None

## 5. FIRE FIGHTING MEASURES

Flash Point: Not applicable

Upper Flammable Limit (UEL): Extremely Flammable

Lower Flammable Limit (LEL): Extremely Flammable

Auto Ignition: Self -Igniting

Rate of Burning: N/D

General Fire Hazards: Aerosol can may explode and release flammable propellant.

Hazardous Combustion Product: May produce irritating fumes in fire.

Extinguishing Media: Foam, Co2 and/or dry chemicals.

Fire Fighting Equipment/Instructions: Use SCBA equipment.

NFPA Rating: (Flammability 4) (Health 3) (Reactivity 2) (MIR 1.4)

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Eliminate all the ignition sources such as electrical, static, frictional sparks and pilot. Isolate the area.

Environmental Precautions: Isolate the spilled area. Prevent additional further leakage or spillage, if safe to do so.

Method for Cleanup & Containment: Wear appropriate protective equipment and clothing during the clean-up. Use non-combustible material like vermiculite, sand, clay or other absorbent material to absorb the spilled liquid.

Additional Information: Follow local and federal regulations with regard to chemical spills.

## 7. HANDLING AND STORAGE

Handling Procedure: Avoid breathing mist or vapors. Avoid prolonged contact with skin. Avoid contact with eye. Wear suitable PPE.

Wash hands thoroughly after handling the product.

Storage Procedures: Keep in a well-ventilated cool place, away from open flame, heat, reactive chemicals and/or other source of ignition.

Prevent electrostatic charge buildup by using common bonding and grounding techniques.

Aerosol container may burst if heated over 130°F. Do not store at temperature below 32°F.

### **8. EXPOSURE CONTROL / PERSONAL PROTECTION**

Occupational Exposure Limits:

ACGIH Components: Use ventilation adequate to maintain TLV.

OSHA Components: No

Engineering Measures: Use fan in confined area. Use local exhaust ventilation.

Personal Protective Equipment (PPE): Utilize suitable protective clothing, and other appropriate PPEs to protect eyes and hands.

Hygiene Recommendations: Use caution appropriate to Aerosols in use and storage. Use protective equipment (apron and boots are optional).

Consider the effect of exposure potentials, handling practices, chemical concentration and ventilation.

### **9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Black

Physical State: Thick Liquid

Vapor Pressure: N/D

Boiling Point: -47°F

Solubility (H2O): Insoluble in water

Freezing Point: N/D

Odor: Aromatic

pH: N/D

Density: N/D

Vapor Density: N/D

Melting Point: N/D

Specific Gravity: N/D

VOC: 39.7%

### **10. STABILITY AND REACTIVITY**

Chemical Stability: Stable under normal conditions.

Conditions to Avoid: Heat, flames and sparks.

Incompatibility: Oxidizing agents and strong chemicals.

Hazardous Decomposition: Carbon monoxide, Carbon dioxide, Phosgene and Nitrogen oxide.

Hazardous Polymerization: Will not occur.

### **11. TOXICOLOGICAL INFORMATION**

Route of Entry: Inhalation, skin ingestion and eyes.

Acute Chronic Toxicity Data: CNS effects includes fatigue, numbness, eye and skin irritation.

Carcinogenicity: No component in this product is a carcinogenic.

NTP: No

IARC Monographs: No

Chronic Toxicity: Not established.

### **12. ECOLOGICAL INFORMATION**

Ecotoxicity: N/D

Persistence and Degradability: N/D

Bioaccumulative potential: N/D

Mobility in Soil: N/D

Other Adverse effects: N/D

### **13. DISPOSAL CONSIDERATIONS**

Disposal Instructions: Follow local and federal disposal regulations. As a non-hazardous liquid waste, it should be solidified with stabilizing absorbent material before disposal.

### **14. TRANSPORTATION INFORMATION**

US DOT Information: ORM-D CONSUMER COMMODITY CLASS 55

UN Number: N/A

Marine Pollutant: N/D

Shipping Name: 911 PRUNING SEAL

Required Label: N/A

### **15. REGULATORY INFORMATION**

Classification: Flammable, Aerosol, Irritant

Hazard Symbol: Exclamation Point, Gas Cylinder, Flame



US Federal Regulations:

OSHA'S Hazard Communication Rule, 29 CFR 1910.1200-Is a combustible liquid, moderate skin irritant, moderate eye irritant and a skin sensitizer.

SARA Title III-This product does contain chemicals subjected to the reporting requirements by SARA Title III, section 313: Toluene, <22%.

**State Regulations:**

California Prop. 65

**WARNING:** This product can expose you to chemicals including TOLUENE, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



## **16. OTHER INFORMATION**

### **SDS History**

Date Prepared: 12/9/2016

Revision Date: 08/27/2018

**Contact Information:** Sunrise Environmental Scientific  
Remit: PO Box 10207 Reno, NV 89510  
Physical: 1175 Industrial Way Sparks, NV 89431  
Phone Number: 775-359-8494 or 800-648-1153  
Web: [SUNRISENV.COM](http://SUNRISENV.COM)

This SDS is designed only as guidance for the products to which it applies. To the greatest extent permitted by applicable law, nothing contained herein creates any legal obligation including contractual obligations, expressed or implied warranties, including any warranties of merchantability or fitness for particular purpose; or confers any intellectual property rights, including rights to use trademarks or a license to use patents, issued or pending. The information contained herein is based on the manufacturer's own study and the work of others, and is subjected to change at any time without further notice. There is no warranty, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein and neither the provider nor the manufacturer are liable to any party for any damages or nature. Including direct, special or consequential damages arising out of or in connection with accuracy, completeness, adequacy or furnishing of any information in this SDS, or in any other way related (directly or indirectly) to this SDS. The receipt and use of this information constitutes consent to these terms and conditions. The recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.