

AB-73

ALUMINUM CLEANER AND BRIGHTENER
LIMPIADAOE DE ALUMINIO Y BRIGHTNER

AB-73 is designed for the removal of anodic and chromate coatings on aluminum. For cleaning trucks and aluminum vans, one part AB-73 should be diluted with twenty parts of water. More soiled surfaces may require stronger dilution. The solution may be either brushed or sprayed. Allow to dwell until a foam blanket occurs.

DIRECTIONS

DIRECTIONS: Test inconspicuous area before use. When diluting, always add AB-73 to water to avoid splashing of product. For cleaning trucks and aluminum vans, one part AB-73 should be diluted with twenty parts water. More soiled surfaces may require stronger dilution. AB-73 may be either brushed or sprayed on and allowed to dwell until a foam blanket occurs. Rinse with water and reapply if necessary. For mirror finish aluminum, test at 1:50 and increase strength gradually. Do not spray on glass or plexiglass. Use ventilation adequate to maintain TLV. Avoid contamination of food or potable water. Dispose of empty container in accordance with local regulations.

PACKAGING

- 1 Gallon 15 Gallon 275 Gallon
 5 Gallon 30 Gallon Other:
 6 Gallon 55 Gallon

For additional information including SDS and Tech Data Sheet scan QR code here →



TRANSPORT INFORMATION

U.N. Number: UN 2922
U.N. Proper Shipping Name: Corrosive Liquids, Toxic, N.O.S., (Hydrofluoric Acid) (Phosphoric Acid)
Transport Hazard Class(es): 8, (6.1)
Packing Group: II



AB-73

ALUMINUM CLEANER AND BRIGHTENER

PART #2015

READ ENTIRE LABEL BEFORE USING
KEEP OUT OF REACH OF CHILDREN

CAUTIONS

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent, cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

INGREDIENTS

Phosphoric Acid 7664-38-2, Hydrofluoric Acid 7732-18-5

HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity:3 Fire:0 Reactivity: 1 Special: N.A

Hazard Symbol(s)



DANGER: POISON!



PO BOX 10207
RENO NV, 89510

Since 1975