



ACRILAX

HIGH GLOSS FLOOR FINISH

ACABADO PARA PISOS CON BRILLO SUPERIOR

**READ ENTIRE LABEL BEFORE USING.
KEEP OUT OF REACH OF CHILDREN**

SAFETY SECTION

SCAN FOR
SDS & INFO



TOXICITY 0

FIRE 0

REACTIVITY 0

SPECIAL NA



WARNING

- SKIN AND EYE IRRITANT
- RESPIRATORY TRACT IRRITANT
- SWALLOWING WILL CAUSE GASTRO-INTESTINAL IRRITATION

Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information. (CAS# Does not contain any hazardous ingredients).



WARNING: This product contains chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information, go to <https://oehha.ca.gov/proposition-65>

Ingredient Name	CAS #
Acrylamide	76-06-1
Di Ethyl Ether	111-90-0

PRODUCT #2035 • BATCH #

TO REORDER CALL US @ 800.648.1153

Now a high gloss without the hazard of slipperiness. Hospitals, invalid homes and department stores can now have beautiful, easy to maintain floors that are slip resistant, water resistant and black mark resistant. **ACRILAX** gives a higher gloss without any polishing or buffing. Easy to apply and maintain. **ACRILAX** brings out the natural and original true beauty of the floors. **ACRILAX** gives a beautiful finish to all floors such as asphalt tile, vinyl, plastic tile, linoleum, rubber tile, cork, composition, marble, terrazzo, as well as varnished wood floors. **ACRILAX** will not darken any floor. Will not water spot. **SAFE AND EASY TO USE.**

DIRECTIONS

Clean floor thoroughly by removing any old wax and soil. Rinse with clear water and allow to dry. Use a medium size string mop or lambs' wool applicator which has been rinsed in clear water and thoroughly wrung out. Allow to dry and then buff if desired. If a high gloss is desired, daily buffing with an electric polishing machine is recommended. For best results, allow the finish to set for 48 hours prior to buffing. Buff with a Palmetto brush. When used in California dilute 4:1 with water.

SHIPPING/ DOT CLASSIFICATION

LIQUID WAX CLASS 55

SUNRISE ENVIRONMENTAL SCIENTIFIC
800-648-1153 **SUNRISENV.COM**
PO BOX 10207 - RENO, NEVADA 89510



FOLLOW US    