

SAFETY SECTION

DANGER: DO NOT INGEST. RESPIRATORY TRACT IRRITANT.
MAY CAUSE SKIN IRRITATION OR BURN.

SCAN FOR SDS
& INFORMATION



TOXICITY	2
FIRE	3
REACTIVITY	1
SPECIAL	NA



DANGER
- FATAL OR TOXIC IF SWALLOWED
- RESPIRATORY TRACT IRRITANT
- MAY CAUSE SKIN IRRITATION OR BURN

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information. (CAS# 68647-72-3, 64742-47-8, 1119-40-0, 627-93-0, 68-476-86-8).



WARNING: This product can expose you to chemicals including Toluene, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SHIPPING/ DOT CLASSIFICATION

LIMITED QUANTITY

Since 1975...



Proudly made
in the USA!

CONTACT US:

800-648-1153

775-359-8494

PO BOX 10207

RENO, NV 89510

SUNRISENV.COM

**PAINT & VARNISH STRIPPER FOR:
WOOD & METAL FURNITURE
APPLIANCES AIRPLANES
AUTOMOBILES BOATS
MACHINERY**

FEATURES

- Attacks wide variety of paints
- Allows strippers to penetrate surface.
- Reduced fumes, less noxious.

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

PRODUCT #1020 NET WEIGHT: 16.5 OZ

T-STRIP

T-STRIP is formulated for ease in removing paints, lacquers, enamels, varnish, shellacs, acrylics, etc., from plaster, masonry, stone, wood, metal, glass or ceramic.

DIRECTIONS

TEST SMALL INCONSPICUOUS PORTION BEFORE USING. SHAKE VIGOROUSLY BEFORE EACH USE. Clean off heavy oil or grease. Make sure surface is dry. Hold can 8 to 10 inches from surface and spray, apply heavy coat. If applicable apply with brush. Allow to remain until entire surface is blistered or wrinkled. Remove with a scraper or cloth or flush with water. If reapplication is necessary, be sure surface is dry. After use, invert can and use short burst to clear valve. **IMPORTANT:** Protect surrounding objects from over-spray as it will attack plastics and asphalt tile. Do not allow scrapings or washing to contact live vegetation.

TO REORDER CALL US AT 800.648.1153

USE ON

- Appliances
- Airplanes
- Automobiles
- Boats
- Machinery

VISIT OUR WEBSITE AT WWW.SUNRISENV.COM

ABOUT US...

Sunrise Environmental Scientific is a supplier of industrial chemical formulations to the Industrial, Institutional and Governmental marketplaces. In business since 1975, SES prides itself in manufacturing the highest quality chemical compounds available today.

Our wide market divergence and eclectic product line demand the utmost in production and sales efficiencies. We continually strive to "Blend the Demands of Industry and Environment", by complying with the most rigid air quality and environmental compatibility requirements in the country.