

# NOT FOR RESALE



# SUNRISE

ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

# PITCH OFF

**AMMONIATED CLEANER SPECIALLY FORMULATED TO REMOVE  
PITCH, TAR AND OTHER RESINOUS MATERIALS FROM TOOLS  
AND EQUIPMENT**

## LIMPIADOR AMONIACO

**READ ENTIRE LABEL BEFORE USING.  
KEEP OUT OF REACH OF CHILDREN**

## SAFETY SECTION

SCAN FOR  
SDS & INFO



**TOXICITY 2**

**FIRE 0**

**REACTIVITY 1**

**SPECIAL NA**



### DANGER

- SKIN AND EYE IRRITANT
- RESPIRATORY TRACT IRRITANT
- MAY CAUSE SKIN BURN OR EYE DAMAGE



**CAUTION:** CONTAINS CAUSTIC AND/OR STRONGLY ALKALINE SUBSTANCES, HARMFUL OR FATAL IF SWALLOWED. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. PROLONGED OR REPEATED CONTACT MAY CAUSE DERMATITIS IN SENSITIVE INDIVIDUALS. PROTECTIVE EQUIPMENT RECOMMENDED.

**INGESTION:** If ingested drink large quantities of water or milk. Call a physician or go to a hospital immediately. **EYES:** Flush with copious amounts of potable water for 15 minutes. See a physician. **INHALATION:** Respiratory irritant. Use ventilation adequate to prevent cough, hoarseness or irritation. **SKIN:** If skin is contacted wash off immediately with soap and water, followed by washing with vinegar. **CLOTHING:** Remove contaminated clothing immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Consult Safety Data Sheet for further information.

Ingredient Name	CAS#
2-Butoxyethanol	111-76-2
Caustic Potash	1310-58-3
Sodium Metasilicate	6834-92-0
Ammonium Hydroxide	1336-21-6
Nonylphenol Ethoxilate	9016-45-9

PRODUCT #2115 • BATCH #

**TO REORDER CALL US @ 800.648.1153**

## DIRECTIONS

**PITCH OFF** is the perfect way to rid equipment of sticky pitch and stubborn tar. **PITCH OFF** is a long-lasting and effective product for the removal of pitch and tar.

**DIRECTIONS:** **PITCH OFF** concentrate is to be diluted 1-2 to 1-5 in water, depending on the degree of buildup and its hardness. Just rub or spray **PITCH OFF** on the surface, allow a few minutes for penetration and wipe off buildup. Agitation with a stiff bristle brush is beneficial in certain cases. Be sure to rinse with clear water after pitch is removed.

## SHIPPING/ DOT CLASSIFICATION

**UN 1760 CORROSIVE LIQUIDS, N.O.S., (CONTAINS SODIUM METASILICATE PENTAHYDRATE), 8, PG III, CLASS 85**

## SUNRISE ENVIRONMENTAL SCIENTIFIC



**800-648-1153 SUNRISENV.COM  
PO BOX 10207 - RENO, NEVADA 89510**