

SAFETY SECTION

DANGER: DO NOT INGEST. RESPIRATORY TRACT IRRITANT. MAY CAUSE SKIN IRRITATION OR BURN.

SCAN FOR SDS
& INFORMATION



TOXICITY 2

FIRE 4

REACTIVITY 0

SPECIAL



DANGER

- DO NOT INGEST
- EXTREMELY FLAMMABLE
- RESPIRATORY TRACT IRRITANT
- MAY CAUSE SKIN IRRITATION OR BURN



DANGER: EXTREMELY FLAMMABLE. Do not spray near sparks, heat or open flames. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. **DO NOT SMOKE WHILE USING.** Turn off stoves, electric tools and appliances, and any other sources of ignition. If container comes in contact with electrical parts, battery terminals, or solenoids, a flash fire may occur. **WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects. **FIRST AID:** If eye contact: Flush with water for 15 minutes, lifting upper and lower lids. Get immediate medical attention. If SKIN CONTACT: Wash affected area immediately with soap and water. If irritation persists, get medical attention. **EXCESSIVE INHALATION:** Remove to fresh air and call

a physician. **IF SWALLOWED:** Do not induce vomiting. Get medical attention immediately. For further information, consult Material Safety Data Sheet. **CONTENTS UNDER PRESSURE:** Avoid prolonged exposure to sunlight and heat from radiators, stoves, hot water and other heat sources. Exposure of heat above 120 Degrees F. may cause can to burst and cause injury. Do not puncture, incinerate or place in a trash compactor. Care should be taken not to store aerosols in automobiles or trunks when interior temperatures reach 120 Degrees F. **NOTICE:** Reports show prolonged exposure to solvents may cause brain and nervous system damage. **DO NOT INHALE.**

SHIPPING/ DOT CLASSIFICATION

LIMITED QUANTITY

Since 1975...



Proudly made
in the USA!

CONTACT US:

800-648-1153

775-359-8494

PO BOX 10207

RENO, NV 89510

SUNRISENV.COM



SUNRISE

ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

MEGA LUBE

HIGH TEMP SPECIALTY LUBRICANT

LUBRICANTE SECO PARA ALTAS TEMPERATURAS

FEATURES

- High temp dry lube
- Withstands temperature up to 600° F
- Withstands up to 10,000 PSI
- Dry film will not attract dirt or dust
- Contains molybdenum disulfide
- Dries in 3-5 minutes
- Excellent protection under severe loads
- Use on any metallic parts

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

PRODUCT #1016

NET WEIGHT: 14 OZ

MEGA LUBE

An extreme range lubricant that withstands temperatures from -110°F to + 600°F. Resists pressures up to 10,000 psi. Inert to water, oil, alkalis and many acids. Dry film coating will not attract dirt or dust. Contains molybdenum disulfide. Provides lubrication even under salt spray conditions.

INDUSTRY USES: Foundries, automotive plants, vehicle maintenance, sewing trades, paper and corrugated converting, textile plants, woodworking, marine, agricultural and military equipment, road equipment, oil drilling equipment, aircraft maintenance, steel mills, mining operations, etc.

DIRECTIONS: Shake can vigorously before application. Surface must be free from all loose rust, oil, grease and old paint. Spray with a sweeping motion, holding can 8 to 10 inches away from surface. Apply a thin uniform coating. Allow to set approximately 3 to 5 minutes before applying a second coat.

IMPORTANT: To prevent clogging: After each use, invert can and spray a few short bursts to clear valve.

TO REORDER CALL US AT 800.648.1153

Ingredient Name	CAS#
Acetone	67-64-1
Propane	74-98-6
Glycol Ether EP	2807-30-9
n-Butane	106-97-8
Isopropyl Alcohol	67-63-0

VISIT OUR WEBSITE AT WWW.SUNRISENV.COM

ABOUT US...

Sunrise Environmental Scientific is a supplier of industrial chemical formulations to the Industrial, Institutional and Governmental marketplaces. In business since 1975, SES prides itself in manufacturing the highest quality chemical compounds available today.

Our wide market divergence and eclectic product line demand the utmost in production and sales efficiencies. We continually strive to "Blend the Demands of Industry and Environment", by complying with the most rigid air quality and environmental compatibility requirements in the country.