

LUBRA 2000

LUBRIANT & SEALANT
LUBRICANTE Y SELLADOR

LUBRA 2000 anti-seize and hi-pressure lubricant is recommended for industrial machinery, electric motors, automotive, farm and construction equipment. LUBRA 2000 protects against extreme heat, galvanic pitting, corrosion and rust. For use on threaded fasteners and as a pipe sealer, gasket seal (both sides), hose connection, etc., under adverse conditions of pressure, moisture and heat conditions up to 2000°F.

SHAKE WELL BEFORE USING

DIRECTIONS

Hold can upright. Squeeze trigger. For best results, keep spray can within 8 to 10 inches from surface to be covered. For pinpoint accuracy use extension tube. Make certain that surfaces to be covered are free from oil, dirt, and grease. For best results, use in temperatures above 65°F. After spraying, turn can upside down, depress valve for several seconds to clean out material left in spray tip.

For additional information including SDS and Tech Data Sheet scan QR code here →



FEATURES:

- Capable to withstanding up to 2000°F
- Up to 15,000 PSI and stable under severe pressure
- Contains micrometals which prevent galvanic pitting and carbon fusion, prevents seizing



LUBRA 2000

LUBRICANT & SEALANT

PRODUCT #1050

NET WEIGHT: 14 OZ (400 g)

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

CAUTIONS

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

INGREDIENTS

Graphite 7782-42-5, Fumed Silica-Amorphous 112945-52-5, Aluminum 4729-90-5, 1, 1, 2, 2 Tetrachloroethylene 127-18-4, Propellant 68-476-86-8, n-Hexane 110-54-3, Isoparaffinic Hydrocarbon

HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity:1 Fire: 1 Reactivity: 0 Special: N.A

Hazard Symbol(s)



TRANSPORT INFORMATION

U.N. Number: UN 1950

U.N. Proper Shipping Name: Aerosol, Flammable

Transport Hazard Class(es): 2.1

Description: UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

SUNRISE ENVIRONMENTAL SCIENTIFIC

800-648-1153 SUNRISENV.COM



PO BOX 10207
RENO NV, 89510

Since 1975