

# NOT FOR RESALE



# SUNRISE

ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

# CLEAR TAC FG

## SYNTHETIC, HIGH SPEED BEARING LUBRICANT

HECHO PARA LA INDUSTRIA DE PROCESAMIENTO DE ALIMENTOS

- **CHEMICAL RESISTANT**
- **NON-STAINING**
- **FOR HIGH SPEED APPLICATION**
- **REPELS WATER AND ICE**

**CAUTION:** CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

**KEEP OUT OF REACH OF CHILDREN**

PRODUCT #1119 NET WEIGHT: 13.5 OZ

## CLEAR TAC FG

**CLEAR TAC FG** is the next great product in **SUNRISE'S** line of premium products made for the food processing industry. The name "**CLEAR TAC FG**" says it all! This translucent formulation is designed for areas where a high-speed, bearing lubricant is required. **CLEAR TAC FG** is multi-purpose, non-melting and waterproof. A high temperature range (-10 to 325°F) allows for use in a high friction environment.

**DIRECTIONS:** Spray a thin film on the surface to be lubricated or protected. To treat hard-to-reach areas, insert extension tube in spray tip. **CLEAR TAC FG** will start forming into grease in seconds. Allow 5 to 10 minutes for product to fully cure.

**TO REORDER CALL US AT 800.648.1153**

### SUGGESTED USES:

- **Food Processing Machinery**
- **Chains**
- **Farm Equipment**
- **Fire Hydrants**
- **Water Lines**

**VISIT OUR WEBSITE AT [WWW.SUNRISENV.COM](http://WWW.SUNRISENV.COM)**

ABOUT US...

Sunrise Environmental Scientific is a supplier of industrial chemical formulations to the Industrial, Institutional and Governmental marketplaces. In business since 1975, SES prides itself in manufacturing the highest quality chemical compounds available today.

Our wide market divergence and eclectic product line demand the utmost in production and sales efficiencies. We continually strive to "Blend the Demands of Industry and Environment", by complying with the most rigid air quality and environmental compatibility requirements in the country.

## SAFETY SECTION

**WARNING:** DO NOT INGEST. RESPIRATORY TRACT IRRITANT. MAY CAUSE SKIN IRRITATION OR BURN.

SCAN FOR SDS  
& INFORMATION



**TOXICITY 1**

**FIRE 1**

**REACTIVITY 0**

**MIR**



The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of



empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

Ingredient Name	CAS#
Isoparaffinic Hydrocarbon	64742-47-13
Hydrocarbon Propellant	68-476-86-8
Mineral Oil FG	8042-47-5

SHIPPING/ DOT CLASSIFICATION

## LIMITED QUANTITY

Since 1975...



Proudly made  
in the USA!

**CONTACT US:**

800-648-1153

775-359-8494

PO BOX 10207

RENO, NV 89510

[SUNRISENV.COM](http://SUNRISENV.COM)