SAFETY SECTION

WARNING: DO NOT INGEST. RESPIRATORY TRACT IRRITANT. MAY CAUSE SKIN IRRITATION OR BURN.







The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty

can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

Ingredient Name	CAS#
Silicon Emulsion	63148-62-9
Isoparaffinic Hydrocarbon	68551-19-9
Propellant	68-476-86-8

SHIPPING/ DOT CLASSIFICATION

LIMITED QUANTITY

Since 1975...



in the USA!

800-648-1153 775-359-8494 PO BOX 10207 RENO, NV 89510 SUNRISENV.COM

CONTACT US:

SUNRISE ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

PAD & SHAKER PRETREAT

GELLED SILICONE SHAKER PAD LUBRICANT

PRETRETA ALMOHADILLA Y SHAKER

FEATURES:

- HIGH SILICONE CONTENT
- STAYS SLICKER LONGER
- EXTENDS THE LIFE OF SHAKER SLINGS
- AUTOMATIC AND MANUAL APPLICATIONS

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

PRODUCT #1126

NET WEIGHT: 16 OZ

PAD & SHAKER PRETREAT

PAD & SHAKER PRETREAT is a clear, non-toxic synthetic spray lubricant designed to lubricate and protect rubber tree-shaker slings. This compound deeply penetrates into rubber and leaves a stable broadcast of synthetic lubricant to provide a slippery barrier for reduced friction on the rubber to rubber surface. It prevents heat build-up during the tree shaking operation and prevents bark damage to the tree. This clean, non-toxic formula can be used with confidence to provide solutions to a multitude of lubrication problems associated with valves, pistons, rings, seals, slides, tracks, hinges, gears, etc.

DIRECTIONS: Point trigger toward target area and spray a thin film into the working surface of the shaker sling. As the lubricants impregnate the surface of the rubber, a shiny wet appearance will be maintained. Re-apply approximately once per hour or as conditions warrant.

When new shaker slings are installed it is recommended to pre-soak the working surface of the rubber with **PAD & SHAKER PRETREAT** two or three times at 1-hour intervals prior to installation.

TO REORDER CALL US AT 800.648.1153

SUGGESTED USES:

 All Manual and Automatic Applications for Tree Shakers

VISIT OUR WEBSITE AT WWW.SUNRISENV.COM

ABOUT US...

Sunrise Environmental Scientific is a supplier of industrial chemical formulations to the Industrial, Institutional and Governmental marketplaces. In business since 1975, SES prides itself in manufacturing the highest quality chemical compounds available today.

Our wide market divergence and eclectic product line demand the utmost in production and sales efficiencies. We continually strive to "Blend the Demands of Industry and Environment", by complying with the most rigid air quality and environmental compatibility requirements in the country.