

NOT FOR RESALE

SUNRISE

ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

CC-32

REMOVES CONCRETE FROM METAL

REMOVEDOR DE CONCRETO

**READ ENTIRE LABEL BEFORE USING.
KEEP OUT OF REACH OF CHILDREN**

SAFETY SECTION

SCAN FOR
SDS & INFO



TOXICITY 3

FIRE 0

REACTIVITY 1

SPECIAL NA

DANGER



- SKIN AND EYE IRRITANT
- RESPIRATORY TRACT IRRITANT
- MAY CAUSE SKIN BURN OR EYE DAMAGE



Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.



WARNING: This product can expose you to chemicals including ethylene oxide, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient Name	CAS#
Hydrochloric Acid	7647-01-0
Ethylene Oxide	75-21-8
Linear Alkylbenzene Sulfonate Acid	68584-22-5

PRODUCT #2011 • BATCH #

TO REORDER CALL US @ 800.648.1153

CC-32 will remove hardened cement from handling equipment such as; bulk cement haulers, redimix equipment, cement mixers and locations in cement manufacturing plants.

DIRECTIONS

• WEAR PROTECTIVE EQUIPMENT •

Face shield, chemical resistant gloves, apron and boots.

CC-32 should be diluted; 1 part with 2 parts water. Apply solution to surface to be cleaned. After foaming action stops, flush with water. Reapply if build-up is excessive. Before using **CC-32**, it is recommended that surfaces around and below area to be cleaned should be tested to make sure no harm will result from splashing of this product.

CAUTION: CONTAINS STRONG ACID

HARMFUL OR FATAL IF SWALLOWED. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. PROLONGED OR REPEATED EXPOSURE MAY CAUSE DERMATITIS IN SENSITIVE INDIVIDUALS.

SHIPPING/ DOT CLASSIFICATION

**UN 1789, HYDROCHLORIC ACID
SOLUTION, 8 PG II CLASS 70**

SUNRISE ENVIRONMENTAL SCIENTIFIC



**800-648-1153 SUNRISENV.COM
PO BOX 10207 - RENO, NEVADA 89510**