



Blending the Demands of Industry and Environment

TECHNICAL DATA SHEET



PACKAGING AVAILABILITY:

Bulk liquid 1g, 6g, 15g,
30g and 55g
drums

PART #2129

QR CODE:



DEEP SEAL

ACRYLIC UNDERCOATER AND SEALER

A new and improved plastic glaze coating that penetrates into the pores giving a hard gloss finish without any slip hazard. It actually makes the floor less slippery than the original floor. Gives protection against oil, grease, medicine and waterborne stains so that the floor will not become permanently damaged. It contains no wax or organic solvents. Will not oxidize or darken. It is non-flammable. Easy to apply. Traffic lanes that have become worn may be gone over without showing any overlaps. Brings out the original beauty of old surfaces. Keeps floors from becoming unattractive due to heavy traffic, spilled food, shifting feet, sweeping, mopping and the like. Prevents the floor from becoming dull, spotted and hard to clean.

FEATURES & BENEFITS:

- 20% Solid compound- Harder more durable.
- Self leveling- Leaves excellent finish.
- Optical intensifiers- Brings out lustre in all top coat finishes.

APPLICATIONS:

This product is an excellent sealer for use on tile, terrazzo, concrete, vinyl or rubber surfaces. This product provides the needed undercoating and sealing of these hard surfaces. Floor finishes and waxes adhere better to surfaces treated with this product.

DIRECTIONS:

After the floor has been thoroughly washed, rinsed and dried, apply **DEEP SEAL** with a short cotton mop or lambs wool applicator. If the floor is porous, a second coat should be applied after the first coat has dried. It will dry with a nice lustre, usually within 20 minutes. To maintain the floor, it is only necessary to damp mop with mop that has been dipped into a solution 1 part of **DEEP SEAL** to 3 parts of water, or buff with a rotary floor machine. Prevents the dirt from becoming permanently imbedded in the floor; it actually seals in the beauty. To remove surface dirt, a mild solution is all that is necessary. When the finish on the floor has become excessively dirty, worn, and it is desired to remove the finish, all that is necessary is to apply a concentrated solution to remove it. There is no difficulty in removing the finish. One part **SUNRISE' TWIN POWER** to ten parts of water will remove this finish. After it has been removed, rinsed and dried, a new coat should be applied. In applying, do not rub in but simply apply with light, even strokes. No special skill is required to put on this seal and finish.

CUSTOMERS WHO USED THIS PRODUCT ALSO USED:

FORMULATION:

Drying agents, levelers, polyethylene and acrylic resins.

TARGET ACCOUNTS:

Warehousing, schools, hospitals, convention centers, department stores, supermarkets.

SPECIAL CAUTIONS:

None.

WWW.SUNRISENV.COM

P.O. Box 10207

Reno, Nevada 89510

Fax: 775-359-6751

1-800-648-1153

775-359-8494

